# N1 015GF BLK POLYAMIDE (PA-6)



### **PRODUCT DESCRIPTION**

Nylon 6 15% Glass Filled Black.

### **FEATURES**

- Glass Filled
- Excellent Mechanical & Chemical properties

### **APPLICATIONS**

- Furniture
- Automotive
- Home appliance

TYPICAL PROPERTIES  PHYSICAL PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUES
Density	D-792	g/cc	1.22
MECHANICAL PROPERTIES			
Tensile Strength Yield	D-638	MPa	120
Elongation Break	D-638	%	3
Flexural Strength,	D-790	MPa	145
Impact Strength (IZOD Notched)	D-256	J/m	7
THERMAL PROPERTIES			
Heat Deflection Temperature - Method B	D-648	°C	205

# Ravago Manufacturing India Pvt Ltd.

96, GIDC Alindra, Manjusar,

Tal. Savali, Vadodara 391775. India

The state of th



## N1 015GF BLK POLYAMIDE (PA-6)



TYPICAL PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUES
FLAMMABILITY			
Flame Rating	UL 94	-	НВ
Glow Wire Testing	IEC 60695-	°C	NA
	2-12		

INJECTION MOLDING CONDITIONS				
Mold Temperature	°C	80 to 100		
Rear Temperature	°C	220 to 230		
Middle Temperature	°C	230 to 240		
Front Temperature	°C	240 to 250		
Nozzle Temperature	°C	250 to 255		

#### **Drying Conditions**

Material can be dried for 4 hours at 90 - 100°C or until moisture level <0.2%.

#### HANDLING AND STORAGE

**Handling:** Maintain good housekeeping. Spilled materials may create a slipping hazard. Remove dust from settling areas to prevent any secondary potential dust explosion or fire hazards. Electrostatic charge may build up during handling. Grounding of equipment is recommended.

**Storage:** Store in a dry place and away from direct sunlight or heat sources.

#### **DISPOSAL CONSIDERATIONS**

**Disposal Method:** It must be disposed of in accordance with Federal, State and local environmental control regulations.

The data and information contained herein are typical average values, based on our current level of knowledge and experience, and do not constitute sales specifications. No liability, warranty or guarantee of product performance is created by this document. It is the buyer's responsibility to inspect and test our products in order to determine the suitability for the buyer's application.

### Ravago Manufacturing India Pvt Ltd.

96, GIDC Alindra, Manjusar, Tal. Savali, Vadodara 391775. India

+919909901581
Format No: F-QC-20

